

GO GO[®]

ULTRA^X



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

De Go Go® Ultra X biedt de prestaties die je mag verwachten van de nummer 1 op het gebied van reismobilititeit. Dit maakt het de ultieme reisscooter, klaar voor al jouw avonturen!



7" massieve banden voor



gebouwd van sterk materiaal



Gemakkelijk te demonteren

Specificaties

Maximale belasting	118 kg
Snelheid	Tot 6,4 km/u
Maximale actieradius	Tot 11,5 km
Draaicirkel	1120 mm
Bodemvrijheid	32 mm
Lengte	1003 mm
Breedte	495 mm
Banden	7" massief voor, 8" massief achter
Aandrijving	Achterwielaandrijving, afgedichte transaxle, 24 volt gelijkstroommotor
Gewicht zonder accu's	36,3 kg
Accu's	Type: Twee 12-volt, deep-cycle Capaciteit: 12 Ah
Meer?	Download het specificaties blad op de website

Kenmerken

- Handige dubbele spanningslader kan de accu zowel aan boord als daarbuiten opladen
- Vederlichte demontage maakt een eenvoudige framescheiding met slechts één hand mogelijk en kan eenvoudig worden gedemonteerd in vijf superlichte stukken voor gemakkelijk transport en opslag
- De op het voorframe gemonteerde zadelpen biedt maximale stabiliteit

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3 %. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Beschikbare kleuren



Rood