

PURSUIT²



PRIDE[®]
MOBILITY
LIVE YOUR BEST[®]

Tel: +31 (0)85-0408630 . Fax: +31 (0)85-0430039
pridemobility.eu . info@prideeurope.nl

Met een topsnelheid van 15 km/u en de mogelijkheid om op één lading 56 km te bereiken, biedt deze wendbare eenheid snel, efficiënt transport en een betrouwbaar uithoudingsvermogen.



Traploos verstelbaar
frees met USB-oplader



Verbeterde LED-verlichting



CTS vering voor en achter

Specificaties

Maximale belasting	159 kg
Snelheid	Tot 15 km/u
Maximale actieradius	Tot 56 km
Draaicirkel	1760 mm
Bodemvrijheid	96 mm
Lengte	1460 mm
Breedte	753 mm
Banden	13" luchtbanden, voor en achter
Aandrijving	Achterwielaandrijving, afgedichte transaxle, 24 volt gelijkstroommotor
Gewicht zonder accu's	100 kg
Accu's	Type: Twee 25-volt lithium ion Capaciteit: 50 Ah
Meer?	Download het specificaties blad op de website

Kenmerken

- Duurzame plastic omhulsels voor het navigeren door struikgewas, weer en transport
- Traploos verstelbare stuurkolom met USB-oplader om uw apparaten onderweg gemakkelijk op te laden
- Luchtbanden gemonteerd op gedeelde velgen voor optimale handling en tractie op elk terrein waar u doorheen rijdt
- 99% van al het onderhoud kan binnen 20 minuten worden uitgevoerd
- Topsnelheid van 15 km/u voor spannende ritten in de vrije natuur

1. Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
3. Battery weight may vary based on battery manufacturer.
4. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.

Beschikbare kleuren

